



# GORI WOOD CLEANER

## Concentrate

Cleaning agent for removal of dirt and incrustations on exterior wooden surfaces. Can be used on various types of wood, stone, concrete, glass, ceramic. Also suitable to use on mineral surfaces, such as mortar, masonry and flagstones. Test colour fastness or discolouring of metal components on the surface to be treated on a non-visible area, before the actual treatment. Apply a test coat before starting treatment, as various cleaning effects are achieved depending on the surface properties.

### PRODUCT DESCRIPTION

**Where to use** On structural wood, framework timber outdoor. All construction timber for structural work (timber located under cover away from damp), timber frames, and outdoor wood (except sill plates or sections in contact with the ground).

**Form supplied** Concentrate - dilute 1:9 with water.

**Pre-treatment** Remove loose dirt and thick layers of incrustations.

**Treatment** Read label and instructions before use. Close can firmly after use.

Dilute GORI Wood Cleaner 1:9 with water. Apply an even layer on a damp surface. Leave to work for a couple of days. Then brush surface with a brush with stiff bristles. If the attack is severe, you can dilute GORI Cleaner 1:3 with water. When the surface is dry (max 15 + 3% humidity), you can apply topcoat.

During application and drying, temperature must be above 5°C and the relative humidity below 80%.

**Application** Apply with brush, watering can, garden spray.

**Thinning** 1:9 with water.

**Cleaning of tools** Soap and water.

### TECHNICAL PRODUCT DESCRIPTION

**Coverage** App. 8-10 m<sup>2</sup>/l – depending on the state of the substrate.

# TECHNICAL DATA SHEET

10130DSC12X04 / #7299



<b>Drying time</b>	Exposure time: 48 hours. Drying time varies depending on amount of product absorbed and ventilation conditions and normal humidity (60%). Deviations may occur depending on temperature, humidity and layer thickness.
<b>Shelf life</b>	5 years in unopened container. Limited shelf life after opening.
<b>Storage</b>	Store and transport frost free in tightly closed container. Store in a dry and cool area away from direct sunlight.

## TECHNICAL DATA

<b>Product type</b>	Wood cleaner.
<b>Density</b>	App. 1.0 g/m <sup>3</sup> at 20°C.
<b>Viscosity</b>	Thin liquid.

## COMPOSITION

<b>Pigments</b>	Bluish in packaging. Will appear colourless during application.
<b>Solvent</b>	Water.
<b>Active ingredients</b>	See product label.

## SAFETY AND ENVIRONMENT

<b>General</b>	Common safety rules for work with paints and varnishes must be observed. Further information is available from our safety data sheet on <a href="http://www.gori.com">www.gori.com</a> .
<b>Disposal</b>	Do not empty into drains or into the environment. Do not pour product waste into sewers, water reserves or soil. Hand in left over product at your local waste disposal. Empty can be recycled (check with your local waste disposal site or your local authorities).

## ADDITIONAL INFORMATION

<b>Wood species</b>	Western Red Cedar, Alaska Yellow Cedar, Larch and similar types of wood contain tannin, which may repel coating and/or staining. Please make a test on a small area before treating, and check the final result.
---------------------	--

# TECHNICAL DATA SHEET

10130DSC12X04 / #7299



Please also note that all softwood may retract or swell up to 12 %. No film can adapt to this kind of movement and therefore a maximum of 18 % humidity is the limit for applying treatment.

Iroko, Teak, Rubber wood and some other wood species contain "oil", which may delay drying and thereby give an uneven surface after application. You can try cleaning the surface with cellulose thinner and then sand with grit 220. Then apply GORI 22 on a small test area. We stress that there is no guarantee for a satisfactory result.

Ipe turns grey after coating with decking oils, but by power-washing after coating is worn down you may return to original colour.

As wood is an organic material, there is no guarantee that the same wood species will react the same way in different areas, when treated/coated/stained. For more information and safety data sheets: [www.gori.com](http://www.gori.com).

---

*The purpose of this Technical Data Sheet is to provide our clients with information about the properties and characteristics of the product. The information provided, is based on tests conducted by us under usage conditions that comply with the prevailing standards. Our recommendations for use are for information only, and in no event shall they take precedence over any specific recommendation taking into account the nature and conditions of a particular site, nor shall they engage PPG's liability. Before all applications of the product, clients should check that this document has not been amended by a more recent version, which takes into account new technical data. This version annuls and replaces all previous versions of Technical Data Sheets relating to this product. Technical Data Sheets can be downloaded from [www.gori.com](http://www.gori.com).*

---

PPG Coatings Danmark A/S  
Gladsaxevej 300  
DK-2860 Søborg  
Tel: +45 39 57 93 00  
[www.gori.com](http://www.gori.com)